

Low Voltage General Purpose Transformers

Type 1-E Encapsulated

Single Phase

Type 1-E general purpose transformers are single phase, resin encapsulated designs suitable for indoor or outdoor applications. Its totally-enclosed, non-ventilated enclosure make it ideally suited for use in areas that contain dust, moisture, or corrosive fumes. Available in ratings through 25kVA, Type 1-E transformers can be mounted in any position for indoor installations and upright positions only for outdoor installations. NEMA 3R enclosure.

Type 1-V Ventilated

Single Phase

1-V general purpose transformers are single phase ventilated units designed primarily for indoor locations (outdoor use of 600 volt class with optional weather-shields). The 1-V utilizes a 220°C insulation system with 150°C rise and is available in ratings of 15 to 167 kVA.



Type 3-E Encapsulated

Three Phase

Type 3-E resin encapsulated, 3-phase transformers are available in ratings of 3 to 75 kVA. Its totally enclosed non-ventilated enclosure makes the 3-E ideally suited for outdoor as well as indoor locations. Type 3-E transformers utilize the 185°C insulation system with 115° rise. 3-E transformers in sizes 3 to 15 kVA are T-T connected. Units installed outdoors must be mounted in upright position. NEMA 3R enclosure.

Type 3-V Ventilated

Three Phase

The 3-phase 3-V ventilated dry-type is available in ratings of 15 to 750 kVA. Its 220°C insulation system (150°C rise) is self-extinguishing. 3-V enclosures are designed for indoor locations (outdoor locations for 600 volt class with the addition of optional weather shields).

Group A: 240x480 Volts to 120/240 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram**	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Single Phase - Encapsulated												
G050A1KF1A01	.050	-	-	6.5	3.875	3.5	A	7	N/A	N/A	1-E	\$51
G075A1KF1A01	.075	-	-	6.5	3.875	3.5	A	7	N/A	N/A	1-E	\$60
G100A1KF1A01	0.1	-	-	6.5	3.875	3.5	A	7	N/A	N/A	1-E	\$65
G150A1KF1A01	.15	-	-	6.5	3.875	3.5	A	8	N/A	N/A	1-E	\$75
G250A1KF1A02	.25	-	-	6.5	4.875	3.875	A	12	N/A	N/A	1-E	\$84
G500A1KF1A02	.5	-	-	6.5	4.875	4.625	A	13	N/A	N/A	1-E	\$105
G750A1KF1A02	.75	-	-	8.375	6	5.5	A	20	N/A	N/A	1-E	\$138
G001K1KF1A02	1	-	-	8.375	6	5.5	A	30	N/A	N/A	1-E	\$169
G1X5K1KF1A02	1.5	-	-	10.5	6.375	6.125	A	40	N/A	N/A	1-E	\$209
G002K1KF1A02	2	-	-	10.5	6.375	6.125	A	40	N/A	N/A	1-E	\$253
G003K1KF7A03	3	Note 1	Note 1	14.125	7.75	8	B	65	N/A	N/A	1-E	\$296
G005K1KF7A03	5	Note 1	Note 1	16	10.375	9.875	B	113	N/A	N/A	1-E	\$446
G7X5K1KF7A03	7.5	Note 1	Note 1	16	10.375	9.875	B	123	N/A	N/A	1-E	\$608
G010K1KF7A03	10	Note 1	Note 1	19	13.375	10.5	B	193	N/A	N/A	1-E	\$701
G015K1KF6A03	15	Note 2	Note 2	19	13.375	10.5	C	216	N/A	N/A	1-E	\$864
G025K1KF6A03	25	Note 2	Note 2	22.375	16.375	14.5	C	375	N/A	N/A	1-E	\$1,150
Single Phase - Ventilated												
G015K2KF6A04*	15	Note 2	Note 2	27	20	16.5	S	210	N/A	WS10MI	1-V	\$1,500
G025K2KF6A04*	25	Note 2	Note 2	37.875	22.5	20	S	310	N/A	WS11MI	1-V	\$1,950
G037K2KF6A04*	37.5	Note 2	Note 2	43.75	22.5	20	S	375	N/A	WS11MI	1-V	\$2,465
G075K2KF6A04*	75	Note 2	Note 2	52.125	26	24.75	S	635	N/A	WS12MI	1-V	\$4,178
G100K2KF6A04*	100	Note 2	Note 2	52.125	26	24.75	S	725	N/A	WS12MI	1-V	\$5,263

Note 1: 1-10% FCBN @ 240V; 2-5% FCBN @ 480V
Note 2: 2-5% FCBN @ 240V; 4-2.5% FCBN @ 480V

* Can be wall-mounted using WMB01MI brackets

** See our web site for details

Group B: 190/200/208/220/380/400/416/440 Volts to 110/120 Volts 50/60 Hz

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram**	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Single Phase - Encapsulated												
G001K1PG1A06	1	-	-	10.5	6.375	6.125	D	40	N/A	N/A	1-E	\$288
G1X5K1PG1A06	1.5	-	-	10.5	6.375	6.125	D	40	N/A	N/A	1-E	\$323
G002K1PG1A07	2	-	-	14.125	7.75	8	D	65	N/A	N/A	1-E	\$386
G003K1PG1A07	3	-	-	16	10.375	9.875	D	113	N/A	N/A	1-E	\$448
G005K1PG1A07	5	-	-	16	10.375	9.875	D	123	N/A	N/A	1-E	\$581
G7X5K1PG1A07	7.5	-	-	22.375	16.375	14.125	D	375	N/A	N/A	1-E	\$795
G010K1PG1A07	10	-	-	19	13.375	10.5	D	193	N/A	N/A	1-E	\$927
G015K1PG1A07	15	-	-	19	13.375	10.5	D	216	N/A	N/A	1-E	\$1,470

** See our web site for details

To order call **1.800.972.0436** or visit **factorymation.com**

No Games, No Gimmicks...

...Just Great Products at Great Prices!!!

Low Voltage General Purpose Transformers

Group D: 600 Volts to 120/240 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram***	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Single Phase - Encapsulated												
G001K1RF8A02	1	-	2-5%	8.375	6	5.5	H	30	N/A	N/A	1-E	\$185
G1X5K1RF8A02	1.5	-	2-5%	10.5	6.375	6.125	H	40	N/A	N/A	1-E	\$238
G002K1RF8A02	2	-	2-5%	10.5	6.375	6.125	H	40	N/A	N/A	1-E	\$280
G003K1RF8A03	3	-	2-5%	14.125	7.75	8	H	65	N/A	N/A	1-E	\$324
G005K1RF8A03	5	-	2-5%	16	10.375	9.875	H	113	N/A	N/A	1-E	\$461
G7X5K1RF8A03	7.5	-	2-5%	16	10.375	9.875	H	123	N/A	N/A	1-E	\$617
G010K1RF8A03	10	-	2-5%	19	13.375	10.5	H	193	N/A	N/A	1-E	\$741
G015K1RF5A03	15	-	4-2.5%	19	13.375	10.5	I	216	N/A	N/A	1-E	\$908
G025K1RF2A03	25	-	4-2.5%	22.375	16.375	14.125	I	375	N/A	N/A	1-E	\$1,462
G025K1RF5A03*	25	2-2.5%	4-2.5%	17.4375	13.625	17.25	J	384	N/A	N/A	1-E	\$1,462
Single Phase - Ventilated												
G025K2RF2A04**	25	2-2.5%	4-2.5%	37.875	22.5	20	V	310	N/A	WS11MI	1-V	\$2,303
G037K2RF2A04**	37.5	2-2.5%	4-2.5%	43.75	22.5	20	V	375	N/A	WS11MI	1-V	\$2,638
G050K2RF2A04**	50	2-2.5%	4-2.5%	43.75	22.5	20	V	425	N/A	WS11MI	1-V	\$3,140
G075K2RF2A04**	75	2-2.5%	4-2.5%	52.125	26	24.75	V	635	N/A	WS12MI	1-V	\$4,323
G100K2RF2A04**	100	2-2.5%	4-2.5%	52.125	26	24.75	V	725	N/A	WS12MI	1-V	\$5,640

* Floor mounted only

** Can be wall-mounted using WMB01MI brackets

*** See our web site for details

Group E: 208 Volts to 120/240 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram**	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Single Phase - Encapsulated												
G500A1HF1A02	0.5	-	-	6.5	4.875	4.625	L	13	N/A	N/A	1-E	\$137
G001K1HF1A02	1	-	-	8.375	6	5.5	L	30	N/A	N/A	1-E	\$214
G1X5K1HF1A02	1.5	-	-	10.5	6.375	6.125	L	40	N/A	N/A	1-E	\$277
G002K1HF1A02	2	-	-	10.5	6.375	6.125	L	40	N/A	N/A	1-E	\$323
G003K1HF1A03	3	-	-	14.125	7.75	8	L	65	N/A	N/A	1-E	\$360
G005K1HF1A03	5	-	-	16	10.375	9.875	L	113	N/A	N/A	1-E	\$520
G7X5K1HF1A03	7.5	-	-	16	10.375	9.875	L	123	N/A	N/A	1-E	\$679
G010K1HF1A03	10	-	-	19	13.375	10.5	L	193	N/A	N/A	1-E	\$819
G015K1HF1A03	15	-	-	19	13.375	10.5	L	216	N/A	N/A	1-E	\$1,012
G025K1HF1A03	25	-	-	22.375	16.375	14.125	L	375	N/A	N/A	1-E	\$1,416
Single Phase - Ventilated												
G025K2HF1A04*	25	-	-	43.75	22.5	20	Q	375	N/A	WS11MI	1-V	\$2,159
G037K2HF1A04*	37.5	-	-	43.75	22.5	20	Q	375	N/A	WS11MI	1-V	\$2,637
G050K2HF1A04*	50	-	-	43.75	22.5	20	Q	425	N/A	WS11MI	1-V	\$3,141
G075K2HF1A04*	75	-	-	52.125	26	24.75	Q	635	N/A	WS12MI	1-V	\$4,383
G100K2HF1A04*	100	-	-	52.125	26	24.75	Q	725	N/A	WS12MI	1-V	\$5,640

* Can be wall-mounted using WMB01MI brackets

** See our web site for details

Group F: 277 Volts to 120/240 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram**	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Single Phase - Encapsulated												
G003K1MF1A03	3	-	-	14.125	7.75	8	M	65	N/A	N/A	1-E	\$371
G005K1MF1A03	5	-	-	16	10.375	9.875	M	113	N/A	N/A	1-E	\$536
G7X5K1MF1A03	7.5	-	-	16	10.375	9.875	M	123	N/A	N/A	1-E	\$701
G010K1MF1A03	10	-	-	19	13.375	10.5	M	193	N/A	N/A	1-E	\$844
G015K1MF1A03	15	-	-	19	13.375	10.5	M	216	N/A	N/A	1-E	\$1,043
G025K1MF1A03	25	-	-	22.375	16.375	14.125	M	375	N/A	N/A	1-E	\$1,459
Single Phase - Ventilated												
G025K2MF1A04*	25	-	-	43.75	22.5	20	R	375	N/A	WS11MI	1-V	\$2,223
G037K2MF1A04*	37.5	-	-	43.75	22.5	20	R	375	N/A	WS11MI	1-V	\$2,719
G050K2MF1A04*	50	-	-	43.75	22.5	20	R	425	N/A	WS11MI	1-V	\$3,236
G075K2MF1A04*	75	-	-	52.125	26	24.75	R	635	N/A	WS12MI	1-V	\$4,625
G100K2MF1A04*	100	-	-	52.125	26	24.75	R	725	N/A	WS12MI	1-V	\$5,823

* Can be wall-mounted using WMB01MI brackets

** See our web site for details



FREE Ground Shipping!*
for online orders over \$500



Low Voltage General Purpose Transformers (cont'd)

Group G: 120x240 Volts to 120/240 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram*	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Single Phase - Encapsulated												
G001K1EF1A02	1	-	-	8.375	6	5.5	K	30	N/A	N/A	1-E	\$221
G1X5K1EF1A02	1.5	-	-	10.5	6.375	6.125	K	40	N/A	N/A	1-E	\$285
G002K1EF1A02	2	-	-	10.5	6.375	6.125	K	40	N/A	N/A	1-E	\$335
G003K1EF1A03	3	-	-	14.125	7.75	8	K	65	N/A	N/A	1-E	\$371
G005K1EF1A03	5	-	-	16	10.375	9.875	K	113	N/A	N/A	1-E	\$536
G7X5K1EF1A03	7.5	-	-	16	10.375	9.875	K	123	N/A	N/A	1-E	\$701
G010K1EF1A03	10	-	-	19	13.375	10.5	K	191	N/A	N/A	1-E	\$844
G015K1EF1A03	15	-	-	19	13.375	10.5	K	216	N/A	N/A	1-E	\$1,043
G025K1EF1A03	25	-	-	22.375	16.375	14.125	K	375	N/A	N/A	1-E	\$1,459

* See our web site for details

Group H: 208 Δ Volts to 480Y/277 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram***	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Three Phase - Ventilated												
G015K5HQ2A04**	15	2-2.5%	4-2.5%	25	20.125	14.125	X	152	RS01MI	WS30MI	3-V	\$1,632
G030K5HQ2A04**	30	2-2.5%	4-2.5%	30.125	20.125	14.125	X	230	RS02MI	WS31MI	3-V	\$1,981
G045K5HQ2A04**	45	2-2.5%	4-2.5%	30.125	20.125	14.125	X	310	RS02MI	WS31MI	3-V	\$1,911
G075K5HQ2A04**	75	2-2.5%	4-2.5%	39.375	26.125	19.125	X	480	RS03MI	WS32MI	3-V	\$3,388
G112K5HQ2A04**	112.5	2-2.5%	4-2.5%	39.375	26.125	19.125	X	600	RS03MI	WS32MI	3-V	\$5,819
G150K5HQ2A04	150	2-2.5%	4-2.5%	46.5	26	20.125	X	760	RS04MI	WS33MI	3-V	\$6,900
G225K5HQ4A04	225	1-5%	2-5%	56	31.25	24.25	Y	1100	RS05MI	WS34MI	3-V	\$8,368
G300K5HQ4A04	300	1-5%	2-5%	56	31.25	24.25	Y	1300	RS05MI	WS34MI	3-V	\$12,469

** Can be wall-mounted using WMB01MI brackets

*** See our web site for details

Group I: 240 Δ Volts to 208Y/120 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram***	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Three Phase - Encapsulated												
G009K3JH8A03	9	-	2-5%	15.875	16.5	9.875	AA	166	N/A	N/A	3-E	\$958
G015K3JH8A03	15	-	2-5%	17.375	19.75	10.5	AA	275	N/A	N/A	3-E	\$1,404
G030K3JH2A03	30	2-2.5%	4-2.5%	26.625	25.25	12.75	BB	422	N/A	N/A	3-E	\$2,579
G045K3JH2A03	45	2-2.5%	4-2.5%	26.5	28.5	14.625	BB	660	N/A	N/A	3-E	\$2,984
Three Phase - Ventilated												
G015K5JH2A04**	15	2-2.5%	4-2.5%	25	20.125	14.125	CC	152	RS01MI	WS30MI	3-V	\$1,632
G030K5JH2A04**	30	2-2.5%	4-2.5%	30.125	20.125	14.125	CC	230	RS02MI	WS31MI	3-V	\$1,977
G045K5JH2A04**	45	2-2.5%	4-2.5%	30.125	20.125	14.125	CC	310	RS02MI	WS31MI	3-V	\$2,411
G075K5JH2A04**	75	2-2.5%	4-2.5%	39.375	26.125	19.125	CC	480	RS03MI	WS32MI	3-V	\$3,388
G112K5JH2A04**	112.5	2-2.5%	4-2.5%	39.375	26.125	19.125	CC	600	RS03MI	WS32MI	3-V	\$4,471
G150K5JH2A04	150	2-2.5%	4-2.5%	46.5	26	20.125	CC	760	RS04MI	WS33MI	3-V	\$5,793
G225K5JH5A04	225	1-5%	2-5%	56	31.25	24.25	DD	1100	RS05MI	WS34MI	3-V	\$8,368
G300K5JH5A04	300	1-5%	2-5%	56	31.25	24.25	DD	1300	RS05MI	WS34MI	3-V	\$12,123

** Can be wall-mounted using WMB01MI brackets

*** See our web site for details

Low Voltage General Purpose Transformers (cont'd)

Group J: 480 Δ Volts to 208Y/120 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram***	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Three Phase - Encapsulated												
G003K3QH8A03	3	-	2-5%	13.375	16	8.375	FF	116	N/A	N/A	3-E	\$527
G006K3QH8A03	6	-	2-5%	15.875	16.5	9.875	FF	143	N/A	N/A	3-E	\$710
G006K3QH3A03	6	2-2.5%	2-2.5%	15.875	16.5	9.875	GG	143	N/A	N/A	3-E	\$710
G009K3QH8A03	9	-	2-5%	15.875	16.5	9.875	FF	166	N/A	N/A	3-E	\$850
G009K3QH5A03	9	-	4-2.5%	15.875	16.5	9.875	HH	166	N/A	N/A	3-E	\$850
G009K3QH3A03	9	2-2.5%	2-2.5%	15.875	16.5	9.875	GG	166	N/A	N/A	3-E	\$850
G015K3QH8A03	15	-	2-5%	17.375	19.75	10.5	FF	275	N/A	N/A	3-E	\$1,149
G015K3QH5A03	15	-	4-2.5%	17.375	19.75	10.5	HH	275	N/A	N/A	3-E	\$1,149
G015K3QH3A03	15	2-2.5%	2-2.5%	17.375	19.75	10.5	GG	275	N/A	N/A	3-E	\$1,149
G030K3QH2A03	30	2-2.5%	4-2.5%	26.625	25.25	12.75	II	422	N/A	N/A	3-E	\$2,383
G045K3QH2A03	45	2-2.5%	4-2.5%	26.5	28.5	14.625	II	660	N/A	N/A	3-E	\$2,827
G075K3QH2A03*	75	2-2.5%	4-2.5%	30.75	30.125	15.625	II	1275	N/A	N/A	3-E	\$3,856
Three Phase - Ventilated												
G015K5QH2A04**	15	2-2.5%	4-2.5%	25	20.125	14.125	JJ	152	RS01MI	WS30MI	3-V	\$1,486
G030K5QH2A04**	30	2-2.5%	4-2.5%	30.125	20.125	14.125	JJ	230	RS02MI	WS31MI	3-V	\$1,805
G045K5QH2A04**	45	2-2.5%	4-2.5%	30.125	20.125	14.125	JJ	310	RS02MI	WS31MI	3-V	\$2,211
G075K5QH2A04**	75	2-2.5%	4-2.5%	39.375	26.125	19.125	JJ	480	RS03MI	WS32MI	3-V	\$3,080
G112K5QH2A04**	112.5	2-2.5%	4-2.5%	39.375	26.125	19.125	JJ	600	RS03MI	WS32MI	3-V	\$4,029
G150K5QH2A04	150	2-2.5%	4-2.5%	46.5	26	20.125	JJ	760	RS04MI	WS33MI	3-V	\$5,313
G225K5QH2A04	225	2-2.5%	4-2.5%	56	31.25	24.25	JJ	1100	RS05MI	WS34MI	3-V	\$7,609
G300K5QH2A04	300	2-2.5%	4-2.5%	56	31.25	24.25	JJ	1300	RS05MI	WS34MI	3-V	\$10,629
G500K5QH2A04	500	2-2.5%	4-2.5%	75	44.5	36	KK	2400	RS06MI	WS35MI	3-V	\$19,772
G750K5QH2A04*	750	2-2.5%	4-2.5%	75	44.5	36	KK	2900	RS06MI	WS35MI	3-V	\$24,586

* Floor mounted only

** Can be wall-mounted using WMB01MI brackets

*** See our web site for details

Group L: 480 Δ Volts to 240 Δ Volts with 120 Volt Lighting Tap

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram***	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Three Phase - Ventilated												
G015K6QJ9B02**	15	2-2.5%	4-2.5%	25	20.125	14.125	LL	152	RS01MI	WS30MI	3-V	\$1,486
G030K6QJ9B02**	30	2-2.5%	4-2.5%	30.125	20.125	14.125	LL	230	RS02MI	WS31MI	3-V	\$1,807
G045K6QJ9B02**	45	2-2.5%	4-2.5%	30.125	20.125	14.125	LL	310	RS02MI	WS31MI	3-V	\$2,211
G075K6QJ9B02**	75	2-2.5%	4-2.5%	39.375	26.125	19.125	LL	480	RS03MI	WS32MI	3-V	\$3,081
G112K6QJ9B02**	112.5	2-2.5%	4-2.5%	39.375	26.125	19.125	LL	600	RS03MI	WS32MI	3-V	\$4,029
G150K6QJ9B02	150	2-2.5%	4-2.5%	46.5	26	20.125	LL	760	RS04MI	WS33MI	3-V	\$5,316
G225K6QJ9B02	225	2-2.5%	4-2.5%	56	31.25	24.25	LL	1100	RS05MI	WS34MI	3-V	\$7,609
G300K6QJ9B02	300	2-2.5%	4-2.5%	56	31.25	24.25	LL	1300	RS05MI	WS34MI	3-V	\$10,629
G500K6QJ9B02	500	2-2.5%	4-2.5%	75	44.5	36	MM	2400	RS06MI	WS35MI	3-V	\$19,772

** Can be wall-mounted using WMB01MI brackets


*** See our web site for details

Group M: 480 Δ Volts to 480Y/277 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram***	Weight (lbs.)	Rodent Screen	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Three Phase - Encapsulated												
G009K3QQ3A03	9	2-2.5%	2-2.5%	15.875	16.5	9.875	NN	166	N/A	N/A	3-E	\$904
G015K3QQ3A03	15	2-2.5%	2-2.5%	17.375	19.75	10.5	NN	275	N/A	N/A	3-E	\$1,292
G030K3QQ2A03	30	2-2.5%	4-2.5%	26.625	25.25	12.75	PP	422	N/A	N/A	3-E	\$2,583
G045K3QQ2A03	45	2-2.5%	4-2.5%	26.5	28.5	14.375	PP	660	N/A	N/A	3-E	\$2,913
Three Phase - Ventilated												
G015K5QQ2A04**	15	2-2.5%	4-2.5%	25	20.125	14.125	QQ	152	RS01MI	WS30MI	3-V	\$1,622
G030K5QQ2A04**	30	2-2.5%	4-2.5%	30.125	20.125	14.125	QQ	230	RS02MI	WS31MI	3-V	\$1,751
G045K5QQ2A04**	45	2-2.5%	4-2.5%	30.125	20.125	14.125	QQ	310	RS02MI	WS31MI	3-V	\$2,415
G075K5QQ2A04**	75	2-2.5%	4-2.5%	39.375	26.125	19.125	QQ	480	RS03MI	WS32MI	3-V	\$3,359
G112K5QQ2A04**	112.5	2-2.5%	4-2.5%	39.375	26.125	19.125	QQ	600	RS03MI	WS32MI	3-V	\$5,691
G150K5QQ2A04	150	2-2.5%	4-2.5%	46.5	26	20.125	QQ	760	RS04MI	WS33MI	3-V	\$5,792
G225K5QQ2A04	225	2-2.5%	4-2.5%	56	31.25	24.25	QQ	1100	RS05MI	WS34MI	3-V	\$8,369
G300K5QQ2A04	300	2-2.5%	4-2.5%	56	31.25	24.25	QQ	1300	RS05MI	WS34MI	3-V	\$12,124

** Can be wall-mounted using WMB01MI brackets

*** See our web site for details

 **FREE Ground Shipping!**
for online orders over \$500



Low Voltage General Purpose Transformers (cont'd)

Group N: 600 Δ Volts to 208Y/120 Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram**	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Three Phase - Encapsulated												
G009K3RH8A03	9	-	2-5%	15.875	16.5	9.875	SS	166	N/A	N/A	3-E	\$853
G015K3RH8A03	15	-	2-5%	17.375	19.75	10.5	SS	275	N/A	N/A	3-E	\$1,164
G030K3RH2A03	30	2-2.5%	4-2.5%	26.625	25.25	12.75	TT	422	N/A	N/A	3-E	\$2,490
G045K3RH2A03	45	2-2.5%	4-2.5%	26.5	28.5	14.625	TT	660	N/A	N/A	3-E	\$2,763
Three Phase - Ventilated												
G015K5RH2A04**	15	2-2.5%	4-2.5%	25	20.125	14.125	UU	152	RS01MI	WS30MI	3-V	\$1,572
G030K5RH2A04**	30	2-2.5%	4-2.5%	30.125	20.125	14.125	UU	230	RS02MI	WS31MI	3-V	\$1,916
G045K5RH2A04**	45	2-2.5%	4-2.5%	30.125	20.125	14.125	UU	310	RS02MI	WS31MI	3-V	\$2,347
G075K5RH2A04**	75	2-2.5%	4-2.5%	39.375	26.125	19.125	UU	480	RS03MI	WS32MI	3-V	\$3,269
G112K5RH2A04**	112.5	2-2.5%	4-2.5%	39.375	26.125	19.125	UU	600	RS03MI	WS32MI	3-V	\$5,691
G150K5RH2A04	150	2-2.5%	4-2.5%	46.5	26	20.125	UU	760	RS04MI	WS33MI	3-V	\$5,633
G225K5RH2A04	225	2-2.5%	4-2.5%	56	31.25	24.25	UU	1100	RS05MI	WS34MI	3-V	\$8,061
G300K5RH2A04	300	2-2.5%	4-2.5%	56	31.25	24.25	UU	1300	RS05MI	WS34MI	3-V	\$12,137

** Can be wall-mounted using WMB01MI brackets

*** See our web site for details

Group O: 600 Δ Volts to 240 Δ Volts

Part Number	kVA	Full Cap. Taps		Dimensions (in.)			Wiring Diagram**	Weight (lbs.)	Rodent Screens	Weather-shield	Type	Price
		FCAN	FCBN	H	W	D						
Three Phase - Encapsulated												
G030K4RJ2A03	30	2-2.5%	4-2.5%	26.625	25.25	12.75	WW	422	N/A	N/A	3-E	\$2,583
G045K4RJ2A03	45	2-2.5%	4-2.5%	26.5	28.5	14.625	WW	660	N/A	N/A	3-E	\$2,913

Accessories

Terminal Lug Kits

Part Number	Typical Sizing	Term. Lugs Cable Range	Qty	Hardware Bolt Size	Qty	Price
LKS1MI	15-37.5 kVA 1-ph	#14-#2	8	¼-20 x ¾	8	\$22
	15-45 kVA 3-ph	#6-250 MCM	4		8	
LKS2MI	50-75 kVA 1-ph	#6-250 MCM	12	¼-20 x ¾	8	\$44
	75-112.5 kVA 3-ph	#6-250 MCM		¼-20 x 1¾	8	
LKS3MI	100-167 kVA 1-ph	#6-250 MCM	3	¼-20 x ¾	3	\$173
	150-300 kVA 3-ph	#2-600 MCM	22	¾-16 x 2	16	
LKS4MI	500 kVA 3-ph	#2-600 MCM	29	¾-16 x 2	18	\$209



Wall Mount Brackets

Part Number	Price
WMB01MI	\$62



Weather Shields

Part Number	Price
WS31MI	\$81
WS33MI	\$85
WS34MI	\$85
WS35MI	\$98

Rodent Screens

Part Number	Price
RS01MI	\$74
RS02MI	\$74
RS03MI	\$74
RS04MI	\$85
RS05MI	\$85
RS06MI	\$98